




**TRIVIEW**  
**TATUNG**  
**15" TFT LCD Monitor**  
**Specifications**



555-A West Lambert Rd, Brea, CA 92821

Tel: (714) 672-0333, Fax: (714) 672-0360

[www.PelikanCam.com](http://www.PelikanCam.com)

Items \ MODEL		TLM-1506
LCD Panel	Screen Size	15 inch (diagonal)
	Viewable size	304.1mm (H) x 228.1mm(V)
	Dot Pitch	0.297mm x 0.297mm
	View angle H/V	140°(H)/125°(V)
	Contrast ratio	500:1
	Brightness	450 cd/m <sup>2</sup>
	Resolution	1024 x 768
	Response Time	8ms
	Display Color	16.2M
Mount	Standard	Desktop Mount (included)
	Options	Rack Mount: TRK-1506 Wall Mount: TWM-157 Pole Mount: TPM-157 Double Arm Wall Mount: TWM-DA1520
Control key define		Channel, Menu, -, +, Power
Power	Input-Voltage	100~240VAC
	Consumption	32W max.
Video	Input	Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
	Output	1 BNC connector for CVBS loop-through output
	OSD	Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
Analog VGA	Input	Analog RGB: 0.707Vp-p / 75Ω, connector: 15 pin D-Sub
	OSD	Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	Plug & Play	DDC2B
	Power Management	VESA DPMS
	Support timing	VESA VGA / SVGA / XGA
Audio	Input/Output	Connector: 2 x RCA connector Level: 1.0Vp-p / 1 KHz
	Speaker	2W x 2 embedded
Mechanical	Dimensions (WxHxD)	356x387x200mm (with base), 356x300x67mm (without base) 14.0x15.2x7.9inch (with base), 14.0x11.8x2.6inch (without base)
	Net Weight	9.0lbs/4.1Kg(with base)
	Others	Rack mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm <sup>2</sup> RoHS compliant

Note: The specifications are subject to change without notice.