

## TLM-1706T TFT LCD Monitor Specification:

| MODEL              |                      | TLM-1706T   |
|--------------------|----------------------|---|
| DESCRIPTION        |                      |   |
| LCD Panel          | Screen Size          | 17 inch (diagonal)  |
|                    | Viewable size        | 337.9mm (H) x 270.3mm(V)  |
|                    | Dot Pitch            | 0.264mm x 0.264mm   |
|                    | View angle H/V       | 160(H)/160(V)   |
|                    | Contrast ratio       | 1000:1  |
|                    | Brightness           | 250 cd/m <sup>2</sup>   |
|                    | Resolution           | 1280 x 1024   |
|                    | Response Time        | 5ms   |
|                    | Display Color        | 16.7M   |
| Control key define |                      | Channel, Menu, -, +, Power  |
| Power Supply       | Input-Voltage        | 100~240V <sub>AC</sub>  |
|                    | Consumption          | 22W max.  |
| Video              | Input                | Composite video, connector: 1 BNC<br>S-video, connector: 1 mini-din 4 pin<br>Level: 1.0Vp-p / 75Ω   |
|                    | Output               | 1 BNC connector for CVBS loop-through output  |
|                    | OSD                  | Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit |
|                    | System Compatibility | Scanning Frequency<br>NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz   |
| Analog VGA         | Input                | Analog RGB: 0.707Vp-p / 75Ω, connector: 15 pin D-Sub  |
|                    | OSD                  | Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit                         |
|                    | Plug & Play          | DDC2B   |
|                    | Power Management     | VESA DPMS   |
|                    | Support timing       | VESA VGA / SVGA / XGA / SXGA  |
| Audio              | Input/Output         | connector: 2 x RCA connector<br>Level: 1.0Vp-p / 1 Khz  |
|                    | Speaker              | 2W x 2 embedded   |
| Mechanical         | Dimension            | 387x402x200mm(with base), 387x338x67mm(without base)  |
|                    | Weight               | 11.0lbs/5.0Kg (with base)   |
| Additional benefit |                      | Rack mountable (19" standard rack, EIA-310-D)<br>VESA mount 100x100mm <sup>2</sup><br>RoHS compliant  |

Note: The specifications are subject to change without notice.