




TATUNG
19" TFT LCD Monitor
Specifications



555-A West Lambert Rd, Brea, CA 92821

Tel: (714) 672-0333, Fax: (714) 672-0360

www.PelikanCam.com

Items \ MODEL		TLM-1906
LCD Panel	Screen Size	19 inch (diagonal)
	Viewable size	376.3mm (H) x 301.0mm(V)
	Dot Pitch	0.294mm x 0.294mm
	View angle H/V	160°(H)/160°(V)
	Contrast ratio	1000:1
	Brightness	300 cd/m2
	Resolution	1280 x 1024
	Response Time	5ms
	Display Color	16.7M
Mount	Standard	Desktop Mount (included)
	Options	Rack Mount: TRK-1906 Wall Mount: TWM-157 Pole Mount: TPM-157 Double Arm Wall Mount: TWM-DA1520
Control key define		Channel, Menu, -, +, Power
Power	Input-Voltage	100~240VAC
	Consumption	40W max.
Video	Input	Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
	Output	1 BNC connector for CVBS loop-through output
	OSD	Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
Analog VGA	Input	Analog RGB: 0.707Vp-p / 75Ω, connector: 15 pin D-Sub
	OSD	Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit
	Plug & Play	DDC2B
	Power Management	VESA DPMS
	Support timing	VESA VGA / SVGA / XGA / SXGA
Audio	Input/Output	Connector: 2 x RCA connector Level: 1.0Vp-p / 1 KHz
	Speaker	2W x 2 embedded
Mechanical	Dimensions (WxHxD)	458x416x215mm (with base), 458x373x77mm (without base) 18x16.4x8.5inch (with base), 18x14.7x3 (without base)
	Net Weight	14.5lbs/6.4Kg (with base)
	Others	Rack mountable (19" standard rack, EIA-310-D)(Open rack only) VESA mount 100x100mm2 RoHS compliant

Note: The specifications are subject to change without notice.