

TLM-1906T TFT LCD Monitor Specification:

DESCRIPTION		MODEL	TLM-1906T
LCD Panel	Screen Size	19 inch (diagonal)	
	Viewable size	376.3mm (H) x 301.0mm(V)	
	Dot Pitch	0.294mm x 0.294mm	
	View angle H/V	160(H)/160(V)	
	Contrast ratio	1000:1	
	Brightness	250 cd/m ²	
	Resolution	1280 x 1024	
	Response Time	5ms	
	Display Color	16.7M	
Control key define		Channel, Menu, -, +, Power	
Power Supply	Input-Voltage	100~240V _{AC}	
	Consumption	25W max.	
Video	Input	Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0V _{p-p} / 75Ω	
	Output	1 BNC connector for CVBS loop-through output	
	OSD	Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit	
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz	
Analog VGA	Input	Analog RGB: 0.707V _{p-p} / 75Ω, connector: 15 pin D-Sub	
	OSD	Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit	
	Plug & Play	DDC2B	
	Power Management	VESA DPMS	
	Support timing	VESA VGA / SVGA / XGA / SXGA	
Audio	Input/Output	connector: 2 x RCA connector Level: 1.0V _{p-p} / 1 Khz	
	Speaker	2W x 2 embedded	
Mechanical	Dimension	458x416x215mm (with base), 458x373x77mm (without base)	
	Weight	14.5lbs/6.4Kg (with base)	
Additional benefit		Rack mountable (19" standard rack, EIA-310-D)(Open rack only) VESA mount 100x100mm ² RoHS compliant	

Note: The specifications are subject to change without notice.